

542,1738

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 August 2004 (05.08.2004)


PCT

(10) International Publication Number
WO 2004/065752 A1

- (51) International Patent Classification⁷: **E21B 10/62** (74) Agent: **MADDERNS**; Level 1, 64 Hindmarsh Square, Adelaide, S.A. 5000 (AU).
- (21) International Application Number: **PCT/AU2004/000069** (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 20 January 2004 (20.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003900227 20 January 2003 (20.01.2003) AU
- (71) Applicant (*for all designated States except US*): **TRANSCO MANUFACTURING AUSTRALIA PTY LTD** [AU/AU]; 3 Hull Court, Lonsdale, S.A. 5160 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **FYFE, George** [AU/AU]; 3 Hull Court, Lonsdale, S.A. 5160 (AU).
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: **ATTACHMENT MEANS FOR DRILLING EQUIPMENT**



(57) Abstract: The invention is an attachment means for a ground drilling or cutting tool (10) that enables cutting elements (11) to be removably secured to the tool (10). The attachment means include a first surface (13) on the cutting element (11), a second surface (14) on the tool (10) upon which the first surface (11) locates, dowel holes (15) in each of the first and second surfaces, dowels (16) that locate in aligned dowel holes between said surfaces, engagement surfaces (17, 18) on the cutting element and tool that extends substantially parallel to the longitudinal axis of the tool and engage to resist side loads applied to the cutting elements (11) and fastening means (19) that secures the cutting elements (11) to the tool (10). The invention provides a means of easily removing the cutting elements (11) from the tool (10) for either replacement or maintenance work.

WO 2004/065752 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*